



THE SAMADHI BATH

the Jueta OVA Floating-tank
model OVA / excellent / UV

The Floating tank consists of 2 parts and is easy to install and maintain. The ideal conditions for installation of a Samadhi-bath is a silent room with a shower and toilet facilities, a tiled non-slip floor and a heating system to keep the room temperature warm at 28 degrees Celsius

The Floating tank:

Is an egg shaped form, consisting of a pool and the cover with a big door to enter the bath. Length: 2.50 meter, width 1.60 meter, height 1.30 meter. Weight empty:

app. 125 kgr. weight full 900 kgr. Build of GFK, puttied by hand; double walled, light and sound proof, 2 underwater-speakers, underwater light 12 volt /10 watt, passive- and active ventilation

The cleaning system:

One micron bag filter, flow through heater 230 Volt /1200W /, Iwaki magn. coupling, pump 6000l/ h, double UV - reactor, dosage pump for the cleaning solution 35% H₂O₂ (hydrogen peroxide with silver ions)

The PowerStation:

Integrated in the filter station 230 Volt, 10 Amp, digital temperature control and digital timer, same for end of session wake up light, GFI, fuses, relays. SPS Siemen Logo. Control panel with green/red start light, filter station covered by a hood in the same colour as the floating tank, wireless nurse-call (150m)

Price for one complete system
OVA Floating tank, Model OVA / excellent UV

Euro 21500.--

excl. Tax / creating / transport / installation /. Epson salt
conditions: payable 10 days before delivery.