



## **THE SAMADHI BATH**

Model OVA / excellent / OZON

The Floating tank consists of 2 parts and is easy to install and maintain. The ideal conditions for installation of a Samadhi-bath is a silent room with a shower and toilet facilities, a tiled non-slip floor and a heating system to keep the room temperature warm at 28 degrees Celsius

### The Floating tank:

Is an Egg shaped form, consisting of a pool and the cover with a big door to enter the bath. Length: 2.50 meter, width 1.60 meter, height 1.30 meter. Weight empty: app. 125 kgr. Weight full 900 kgr. Build of GFK, putted by hand, double walled, light and sound proof, 2 underwater-speakers, underwater light 12 volt /10 watt, passive- and active ventilation

### The cleaning system:

One micron bag filter, flow through heater 230 Volt /1200W, Iwaki magn.-Coupling, pump 6000l/ h, **OZON**- reactor with Venturi nozzle, dosage pump for the cleaning solution 35% H<sub>2</sub>O<sub>2</sub> (hydrogen peroxide )

### The power station:

Integrated in the filter station 230 Volt, 10 Amp, digital temperature control and digital timer, same for end of session wake up light, GFI, fuses, relays. SPS Siemens Logo. Control panel with green/red start light, filter station covered by a hood in the same colour as the Floating tank, wireless nurse-call (150m)

Price for one complete system

OVA Floating tank, model OVA / excellent OZON

**Euro 21500.--**

excl. tax / crating / transport / installation / Epson salt

Conditions: payable 10 days before delivery.