



Proposal: Samadhi Bad

Model: OVA / excellent

With the Model OVA / excellent, after each use the floating tank will be filtered and the solution reheated within 30 minutes. During the floating process, the filterstation rests but can be switched on from the inside of the floating tank very simply with a pneumatic air switch.

At the same time this Jacuzzi-massage is warming up the whole bath. After the floating time is over, the guest will be waken up through a signal (flashing) light (4 min.) and immediately the filter station gets in to active modus. The disinfectant hydrogen peroxide with silver ions will be injected automatically directly after ending the floating session. Additionally every night filtering (up to 3 hours) with Ozone / UV irradiation of the sole bath

USP's:

- 1. An egg-shaped floating tank hand-made with fibre glass**
Double walled for sound- heat- and light isolation with large entrance door.
- 2. Patented cleaning system, made from stainless steel**
 - 2.1. The automatic control of the disinfection and filtering after each use of the bath guarantees a high standard of cleanliness.
 - 2.2. The night filtering with **OZON** has a strongly sterilization effect, therefore the use of the disinfectants gets highly reduced.
 - 2.3. The extremely fine bag filter (1 micron) removes the very smallest particles out of the sole bath and if necessary it can be also filled with activated charcoal.
- 3. Flow through heater (with transmission oil) heats up to 110 degree of Celsius**
This animates the water and makes a warm underwater massage possible. There are no heating mats and electromagnetic fields, no heavy current on the floating tank. Heater works combined with an electromagnetic coupled filter pump 5000 litres / hour.
- 4. Pneumatic switches with light, music, Jacuzzi and nurse call**
Easy use for everybody inside of the floating tank (to find as well into the dark).
- 5. Ventilation by vacuum (12 Volt / 0,7 Watt) sucks the used air out of the tank**
Activ modus: 17 cubic meter / hour; - passive modus: with convection.
- 6. Two stereo underwater loudspeaker with frequency switch**
A very good underwater tone transmission gets a fantastic sound quality.
- 7. Fully automatic controlling system in waterproof case**
With SPS-control (from Siemens), FI-switch, protective relays for the pump motor, safety devices, solid state relays - waterproof case integrated into the filter station.
- 8. Peristaltic pump**
Automatic addition of the disinfectants into the filter system
- 9. Extended remote control**
The installation is possible also out of the floating room – with digital temperature controller, digital timer for the floating time and start button.
- 10. Nurse call over radio controller, Range up to 150 meter**